

SYSTEM **KAN-therm**

Innovative water
and heating solutions



Novopress Press Tool **ACO203XL**

Ladies and Gentleman

We have the pleasure to inform You that we have introduced new tools for assembly of **KAN-therm Steel** and **KAN-therm Inox** systems.

Technical characteristics:



Diameter range	12 – 108mm
Crimping force	32kN
Piston stroke	40 / 80mm (adjustable – 2 steps)
Length	460mm
Height	113mm
Width	83mm
Weight	3.9kg with battery
Device power	450W
Power supply	18V battery
Battery type	18V Li-Ion 3.0Ah
Battery operating time	up to 250 clamps*
Battery charging time	about 60 minutes
Battery status	LED indicator in the button
Additional options	Bluetooth, working with the Novocheck App

TECHNOLOGY OF SUCCESS





Novocheck application:

The Novocheck application connects the press tool with a smartphone or tablet, making it possible to monitor on a regular basis the status of the tool and the connections made:

- device working time,
- remaining battery charge,
- tool temperature,
- press cycle counter,
- analysis of the correctness of connections made,
- recording the individual events in the device log.

ACO203XL assembly method:

Drive	ACO203XL Press Tool with Bluetooth + 2x battery 18V Li-Ion 3.0Ah + charger 230V + case: code 47178-301							
Diameter	Jaw		Adapter		Steel	Inox	Steel Sprinkler	Inox Sprinkler
	Type	Code	Type	Code				
[mm]	Type	Code	Type	Code				
12	Jaw M12 type PB2	45489-301	-	-				
15	Jaw M15 type PB2	45490-301	-	-				
18	Jaw M18 type PB2	45491-301	-	-				
22	Jaw M22 type PB2	45492-301	-	-				
28	Jaw M28 type PB2	45493-301	-	-				
35	Jaw M35 type PB2	45494-301	-	-				
	Collar jaw HP35 type PSL Snap On	44359-50						
42	Collar jaw M42 type PSL Snap On	43975-301	ZB203	43610-301	+		-	-
	Collar jaw HP42 type PSL Snap On	44224-50						
54	Collar jaw M54 type PSL Snap On	44131-301	ZB203	43610-301	+		-	-
	Collar jaw HP54 type PSL Snap On	44225-50						
66,7	Collar jaw M66,7 type PSL Snap On	45184-50	ZB221	44967-301				
76,1	Collar jaw M76,1 type PSL Snap On	44345-301						
88,9	Collar jaw M88,9 type PSL Snap On	44346-301						
108	Collar jaw M108 type PSL Snap On	44347-301	ZB221	44967-301				
			ZB222	44970-301				

! The diameter of 108 mm should be pressed in 2 stages (first with ZB221 adapter and second with ZB222 adapter) using the same jaw!



KAN Sp. z o.o.

ul. Zdrojowa 51, 16-001 Białystok-Kleosin
tel. +48 85 74 99 200, fax +48 85 74 99 201
e-mail: kan@kan-therm.com

TECHNOLOGY OF SUCCESS



www.kan-therm.com

ISO 9001